



WONDERTEX PREM FILL & FINISH

FILLER AND SMOOTHER

- + HIGH FILLING POWER
- + SMOOTH FINISH
- + EASY SANDING
- + LOW SHRINKAGE
- + FAST SETTING

TECHNICAL DEFINITION

Filler and smoothing compound for interior use. Designed for filling joints and surface defects, and for finishing to obtain a smooth, even surface.

SUBSTRATES

Suitable for: plasterboard joints, plaster, most common interior substrates. Surfaces must be clean, dry, sound and free from dust.

TECHNICAL PROPERTIES

- Working time: approx. 60 minutes
- Super fine for a smooth finish
- Minimal shrinkage, reducing risk of cracking
- Easy sanding for surface preparation
- Fast setting for quicker sanding and finishing

SAFETY

Use in well-ventilated areas. Avoid inhalation of dust during mixing. In case of contact with eyes, rinse thoroughly with water.

APPLICATION

The suggested mix ratio is 1 part water to 1.75 parts powder (4.5 litres of water per 7.5 kg bag and 9 litres of water per 15 kg bag). Mix thoroughly until a smooth lump free consistency is achieved, leave for 5 minutes then mix again. Apply with suitable tools to fill joints and smooth surfaces. Allow to set, then sand if necessary.

STORAGE

9 months in unopened packaging in a dry place, avoiding exposure to high temperature and frost.

PACKAGING

7.5kg and 15 kg bags.

	premfll & finish	premfll texture	premfll adhesive	premfll finish	premfll filler
sizes	7.5kg & 15kg	25kg	12.5kg	25kg	12.5kg
bonding	•		•		
repairing	•			•	•
jointing	•			•	•
filling	•				•
smoothing	•	•		•	
snagging	•			•	
texturing		•			
working time	60mins	180mins	60-90mins	180mins	60-90mins
apply 2nd coat	120-250mins	n/a	n/a	3-5hours	n/a

