



WONDERTEX FIBRELASTIC

READY-MIXED FILLER

- + HIGH-FIBRE CONTENT
- + PERMANENT ELASTICITY
- + EXCELLENT ADHESION
- + DESIGNED FOR «LIVE CRACKS»

TECHNICAL DEFINITION

Ready-mixed filler with a high resin and glass fibre content for all types of interior and exterior filling works. It has permanent flexibility allowing it to tolerate movements of the substrate without cracking.

COMPOSITION AND APPEARANCE

Emulsion resin, calcium carbonate, fibreglass and various additives with off-white colour.

SUBSTRATES

Ideal for plaster, masonry, concrete, cellular concrete, wood, cement render, plasterboard, roughcast, old painted surfaces, silico-limestone brick. The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally cleaned and primed if necessary.

COVERING AFTER USE

Can be covered with any type of paint or plaster base or ready-to-use fillers.

TECHNICAL PROPERTIES

- Density: 1.3.
- pH: 6.
- Permanent elasticity.

APPLICATION

The application and drying temperature must be between 8° C and 35° C. Do not apply outdoors during showery periods. Do not cover over with cement-based render because of the particle size and the glass fibres it contains, the finish will not be completely smooth.

DRYING TIME

Depends on substrate, weather conditions and application thickness; approximately 24 hours for a 1 mm layer.

STORAGE

12 months in unopened original packing protected from frost and extreme heat.

PACKAGING

310ml cartridges
1kg buckets



USE



MANUAL APPLICATION



LIVE CRACKS



USAGE



APPLICATION TEMPERATURE

