



WONDERTEX MULTI PURPOSE INTERIOR FILLER

FILLER AND SMOOTHER

- + EASY TO APPLY
- + NO SHRINKAGE
- + EXCELLENT ADHESION
- + VERY HIGH-QUALITY FINISH



USE



MANUAL APPLICATION



THICKNESS



USAGE



APPLICATION TEMPERATURE

TECHNICAL DEFINITION

Multi-purpose interior filler for: filling holes, cracks, chases, fixing and stick, pasting polystyrene, roses, cornices, finishing.

COMPOSITION AND APPEARANCE

Powder filler composed of plaster, calcium carbonate, resin, cellulose fibre and various additives. Final mix has a white paste.

SUBSTRATES

All types of interior substrates: plaster, plasterboards, plaster blocks, concrete, cement rendering, concrete blocks, aerated concrete, brick, earthenware, etc... The substrate must not be frozen or overheated. It should be dry, stable and dust free, and additionally degreased and primed if necessary.

COVERING AFTER USE

Can be covered with any type of paint, plaster-based and finishing filler and wallpaper adhesive. For tiling, choose an adhesive suited to plaster substrates.

TECHNICAL PROPERTIES

- Grain size: fine.
- Adhesion: complies with standard NFT 30 608.
- pH: neutral.
- Setting time: 50 min - 1 h 10 min.
- Bending: 3 N/mm².
- Compression: 7 N/mm².

MIXING

0.5 to 0.6 litre of water for 1 kg bag (2.5-3 litres of water for 5 kg, 7.5-9 litres for 15 kg bag) depending on the type of work. For filling, less water you put into the mixture, less the filler shrinks.

DRYING TIME

Depends on substrate, weather conditions and application thickness; approximately 8-12 hours per 10 mm layer.

STORAGE

9 months in original unopened packing protected from damp.

PACKAGING

- 1 kg bags
- 5 kg bags
- 15 kg bags

