



WONDERTEX QUICK DRY FILLER

- + WITHOUT SHRINKAGE
- + CELLULOSE FIBRE
- + EXTRA THIN
- + EXCELLENT GLIDE
- + EASY TO SAND

TECHNICAL DEFINITION

Interior powder filler for filling cracks, holes and dents of all sizes.

COMPOSITION AND ASPECT

Powder compound composed of plaster, calcium carbonate, mineral filler, cellulose, and various adjuvants. The resulting colour is white.

SUBSTRATES

All types of unworked or painted interior substrates: plaster, plaster boards, plaster bricks, concrete, cement compounds, concrete blocks, aerated concrete, bricks, terracotta, etc. The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary.

COVERING AFTER USE

Can be covered by all types of paints, plaster-based fillers, textured ready-mixed, wallpaper adhesives. Tile adhesives must be suitable for plaster substrates.

TECHNICAL PROPERTIES

- pH: neutral.
- Easy sanding.
- Adhesion: complies with NF T30-608.

MIXING

0.5 litres of water per 1 kg bag (2 volumes of powder for 1 volume of water).

DRYING TIME

Approximately 6 hours for 1 cm of thickness, depending on substrate and ambient conditions.

STORAGE

12 months in original, unopened packaging in a dry place.

PACKAGING

2 x 1 kg bags



USE



ANY THICKNESS



APPLICATION TEMPERATURE



1 kg/m²/mm

USAGE FOR FILLING



400 g/m²

USAGE FOR JOINTING

