



WONDERTEX WOOD REPAIR FILLER

ALL TYPES OF WOOD

- + INTERIOR/EXTERIOR
- + LOW SHRINKAGE
- + VERY HIGH-QUALITY FINISH



USE



MANUAL APPLICATION



ANY THICKNESS



DRY-TO-RECOAT



APPLICATION TEMPERATURE

TECHNICAL DEFINITION

Powdered filling and repair plaster for treating holes and cracks in wood.

Can also repair broken corners or reconstitute missing parts.

COMPOSITION AND APPEARANCE

Plaster, mineral filler, resin and various additives. The resulting mix is brown.

SUBSTRATES

All types of wood. The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary.

COVERING AFTER USE

All types of paint, varnish and wood stain.

TECHNICAL PROPERTIES

- Working time: 30 minutes.
- Drying time before painting: 24-48 hours (after complete drying).
- Adhesion: >0.8 MPa in accordance with EN 16566.

PRECAUTIONS FOR USE

Do not apply at humidity levels of above 80%. Do not apply to damp substrates.

The mix must be covered. Apply a primer beforehand on untreated wood.

MIXING

0.4 L of water for 1 kg of powder.

DRYING TIME

It depends on the ambient conditions, the type of substrate and the thickness of application.

A second layer of 5 mm thickness can be applied 3 hours after the first layer under normal conditions.

STORAGE

12 months in the original, unopened packaging.

PACKAGING

1 kg boxes

