



WONDERTEX WOOD REPAIR FILLER

READY-MIXED WOOD FILLER

- + INTERIOR/EXTERIOR
- + LOW SHRINKAGE
- + VERY HIGH-QUALITY FINISH

TECHNICAL DEFINITION

Ready-mixed filler for repairing small holes and cracks in wood.

COMPOSITION AND APPEARANCE

Water, mineral filler, emulsion resin, dispersant and various additives. The colour is beige.

SUBSTRATES

All types of wood. The substrate must not be frozen or overheated. It should be dry, stable and dust-free, and additionally degreased and primed if necessary.

COVERING AFTER USE

All types of paint, varnish and wood stain.

TECHNICAL PROPERTIES

- Easy to sand.
- Adhesion: >0.8 MPa in accordance with EN 16566.

PRECAUTIONS FOR USE

Do not apply at humidity levels of above 80%. The mix must be covered. Apply a primer on untreated wood beforehand.

DRYING TIME

Depends on the ambient conditions, the type of substrate and the thickness of application. Second layer of 1 mm can be applied 12 hours after the first layer under normal conditions. Drying time before painting: 48 hours (after complete drying).

STORAGE

12 months in the original, unopened packaging, protected from frost and high temperatures.

PACKAGING

1 kg pails
300gr tubes



USE



MANUAL APPLICATION



THICKNESS



DRY-TO-RECOAT



APPLICATION TEMPERATURE

